

УДК 621.313.13

Mashkovskyi Roman¹, Kozlov Volodymyr²

¹ Phd Student, NU "Zaporizhzhia Polytechnic"

² PhD (Tech.), assistant professor NU "Zaporizhzhia Polytechnic"

OVERVIEW OF DESIGNS AND TECHNICAL SOLUTIONS FOR IMPLEMENTING AN ELECTRONIC SPEED CONTROLLER (ESC) FOR BRUSHLESS DIRECT CURRENT (BLDC) MOTORS

Brushless DC (BLDC) motors are noteworthy for their high efficiency, precision, and durability. Unlike traditional brushed motors, BLDC motors utilize a rotating permanent magnet in the rotor and stationary coils on the stator,

eliminating the need for brushes and commutators. This configuration minimizes wear, reduces maintenance, and provides superior energy efficiency. The precise speed and torque controllability make BLDC motors especially suitable for applications requiring dependable and continuous operation, such as air conditioners, household appliances, drones, and electric mobility devices. In light of this, the implementation of robust Electronic Speed Controllers (ESCs) is vital to fully harness the performance advantages of BLDC motors.

ESCs serve as the control backbone for BLDC motors, managing key operational parameters like speed, direction, and torque. By periodically switching currents between motor phases, ESCs ensure smooth rotation and stable operation. Control can be achieved either through sensor-based feedback, using components such as Hall effect sensors or encoders, or sensorless methods relying on back electromotive force detection. ESCs interact with broader control systems via communication protocols such as PWM, UART, or CAN, exhibiting pertinence across applications that range from simple remote-controlled devices to complex, multi-motor systems. Safety features like undervoltage lockouts, current limits, and thermal cutoffs protect both the motor and ESC components. Additionally, advanced programmable ESCs enable precise customization, allowing users to tailor parameters such as acceleration curves and braking force to meet specific use cases.




Figure 1 – ESC structure

The operational success of ESCs is dependent on their key components, which include power management systems, microcontroller units, gate drivers, and switching transistors. Capacitors play a crucial role in smoothing voltage fluctuations, while voltage regulators ensure consistent power delivery to ESC logic circuits and sensors. The microcontroller unit (MCU) serves as the ESC's central processing unit, interpreting input signals, generating PWM outputs,

controlling motor phases, and executing safety protocols - examples of popular MCU families include STM32, ATmega, and Infineon XMC series. Gate drivers amplify signals from the MCU to efficiently switch power transistors such as MOSFETs and IGBTs, which handle power delivery to motor phases. MOSFETs are commonly used for low-voltage ESCs due to their high efficiency and low conduction losses, while IGBT transistors, along with emerging technologies such as GaN (Gallium Nitride) and SiC (Silicon Carbide), offer enhanced performance for heavy-duty industrial applications.

Thermal management, application-specific needs, and software integration are critical considerations in ESC design. Effective heat dissipation is ensured through strategies like heatsinks or active cooling systems to maintain system reliability. Lightweight designs are essential for drones, whereas industrial ESCs must prioritize high current-handling capacity and durability. Advanced algorithms such as Field-Oriented Control (FOC) offer precise and adaptive motor control, optimizing performance across diverse settings. Recent developments are indicative of a growing trend toward integrating high-performance materials such as GaN and SiC into ESC technology, delivering improvements in switching speeds, thermal performance, and overall system efficiency. Sensorless control and real-time monitoring are also gaining traction, paving the way for smarter and self-adaptive ESC designs that can support increasingly complex applications.

Despite the diversity in ESC designs and capabilities, their functional architecture consistently follows a core structural schema. This modular approach integrates similar types of components, including power management, switching devices, gate drivers, and a microcontroller unit, regardless of the specific application or performance requirements. Such a standardized framework not only ensures compatibility across various systems but also allows flexibility to innovate within the overarching ESC design paradigm. As ESC technology continues to evolve, this foundational structure will remain at the heart of future advancements, driving the development of more efficient, precise, and adaptive control systems for BLDC motors.

СПИСОК ВИКОРИСТАНОЇ ЛІТЕРАТУРИ

1. The MathWorks, Inc. Introduction to Brushless DC Motor Control [Електронний ресурс]. Режим доступу: <https://www.mathworks.com/campaigns/offers/next/introduction-to-brushless-dc-motor-control.html> (дата звернення: 29.03.2025).
2. Matsui N. Sensorless PM brushless DC motor drives. / N. Matsui // IEEE Transactions on Industrial Electronics. - 1996. №43(2). - pp. 300-308. DOI: doi.org/10.1109/41.491354
3. Shrutika C. Back-EMF estimation based sensorless control of Brushless DC motor. / C. Shrutika, S. Matani, S. Chaudhuri, A. Gupta, S. Gupta, N. Singh //

2021 1st International Conference on Power Electronics and Energy (ICPEE). - 2021. DOI: doi.org/10.1109/ICPEE50452.2021.9358657

4. Gamazo-Real J. Position and speed control of brushless DC motors using sensorless techniques and application trends. // J. Gamazo-Real, E. Vázquez-Sánchez, J. Gómez-Gil // *Sensors*. - 2010, №10(7). - pp. 6901-6947. DOI: doi.org/10.3390/s100706901

5. Lee W. GaN-based single phase brushless DC motor drive for high-speed applications. // W. Lee, D. Han, B. Sarlioglu // 40th Annual Conference of the IEEE. - 2014. DOI: doi.org/10.1109/IECON.2014.7048700

6. Östling M. SiC power devices - Present status, applications and future perspective. / M. Östling, C.-M. Zetterling, R. Ghandi // 2011 IEEE 23RD INTERNATIONAL SYMPOSIUM ON POWER SEMICONDUCTOR DEVICES AND ICS (ISPSD). - 2011. DOI: doi.org/10.1109/ISPSD.2011.5890778

7. Lumbreras D. Efficiency Comparison of Power Converters Based on SiC and GaN Semiconductors at High Switching Frequencies. / D. Lumbreras, J.i Zaragoza, N. Berbel, J. Mon, E. Galvez, A. Collado // 2021 IEEE 30th International Symposium on Industrial Electronics (ISIE). - 2021. DOI: doi.org/10.1109/ISIE45552.2021.9576446

8. Wu R. STM32 microcontroller-based closed-loop speed control drive system design for FOC motors. / R. Wu, Y. Chen, H. Ke // 2022 IEEE Asia-Pacific Conference on Image Processing, Electronics and Computers (IPEC). - 2022. DOI: doi.org/10.1109/IPEC54454.2022.9777600

9. Awaar V. Real-Time BLDC Motor Control and Characterization Using TMS320F28069M with CCS and GUI. / V. Awaar, N. Jampally, H. Gali, R.i Simhadri // 2022 IEEE 2nd International Conference on Sustainable Energy and Future Electric Transportation (SeFeT). - 2022. DOI: doi.org/10.1109/SeFeT55524.2022.9908662

10. Malyi, O., Pospeeva, F., Furmanova, N., Onyshchenko, V., Zaluzhnyi, M., & Ivanov, V.. (2024). *Metodyka peredproiektnoho vyboru komponentiv FPV kvadrokopternoho typu za zadanymy znachennyamy tiah, shvydkosti ta chasu polotu* [Methodology of pre-design selection of components of FPV quadcopter for thrust, speed, and flight time values]. *Elektrotehnika ta elektroenerhetyka*, 1, 35–49. DOI: doi.org/10.15588/1607-6761-2024-1-4 (in Ukrainian.)

11. Mashkovskiy, R., & Kozlov, V. (2024). *Porivnialnyi analiz proshyvoh ESC rehuliatoriv dlia bezkolektornykh dvynuhiv postiinoho strumu u mul'tykopterakh* [Comparative analysis of ESC firmware for brushless DC motors in multicopters]. *Suchasni problemy i dosiahennia v haluzi radiotekhniki, telekomunikatsii ta informatsiynykh tekhnolohii: XII Mizhnarodna naukovo-praktychna konferentsiia*, 10-12 hrudnia, 123–127. (in Ukrainian.)